



MFM SPRAY ADHESIVE™

LOW-VOC CONTACT ADHESIVE

MFM Building Products Corp. manufactures a wide range of innovative waterproofing products for the building industry. Founded in 1961, MFM products are engineered for superior performance and ease of installation.

DESCRIPTION

MFM Low-VOC Spray Adhesive™ is designed and tested for use with all MFM self-adhering products. Use to enhance adhesive properties and extend the application temperature range. This high strength, fast tack, high shear adhesive is ideal for use with Peel & Seal®, SubSeal™, FlexClad®, WindowWrap® and other MFM Products. High temperature rated, fast tack and VOC compliant.

APPLICATION

Follow Instructions Carefully

- Shake can thoroughly for 60 seconds before use
- Surface for application should be clean and dry
- Hold can perpendicular to substrate approx. 8"-12" (20-30 cm) from the surface
- Apply a light, even coating to the substrate at temperatures above 35°F (1.7°C)
- DO NOT spray directly onto self-adhering membrane
- Avoid excessive build-up or puddles on substrate
- Before applying self-adhering membrane, allow spray adhesive to cure for 2-3 minutes, depending on humidity and wind conditions, or until the surface no longer appears or feels wet – do not exceed more than 10 minutes
- Apply the self-adhering membrane onto the substrate and apply even pressure to the entire membrane with a hand roller
- Monitor adhesion as you go – stop installation if the membrane is not properly adhering

MFM Low-VOC Spray Adhesive must cure 2-3 minutes before membrane is applied.

PACKAGING

MFM Low-VOC Spray Adhesive is available in a 14 oz. (397 grams) aerosol spray can. Packaged 12 cans per carton.

WARNINGS

- Roof work is dangerous – work carefully
- Keep cans in a cool, well ventilated area at 70°F (21°C) for optimum performance – do not store above 122°F (50°C)
- Follow warnings and instructions on can
- **DO NOT** spray adhesive in eyes or near face
- **DO NOT** puncture or incinerate container
- **DO NOT** dispose of empty container in trash compactor
- Dispose empty containers in accordance with applicable local, county, state and federal regulations

For exterior use only. Use with adequate ventilation. Keep out of reach of children. Read and understand all information on can label before use.

PRODUCT DATA

Application Temperature	<35°F (<1.7°C)
Bonding Time	5-10 minutes
Coverage per Can	50-60 ft ² (4.6-5.6 m ²)
VOC Content	25.15% by volume
VOC Compliant CARB/OTC	Yes
Recyclable Packaging	Yes
Ozone-Depleting Compounds	No
Packaging	14 oz. aerosol can (397 grams)
Shipping Quantity	12 cans per carton
Shipping Designation	Class 55
Weight per Can	1 lb. (0.45 kg)
Weight per Carton	14.5 lbs. (6.6 kg)
Shelf Life	1 Year+

PRODUCT NUMBER | PRODUCT UPC CODE

90005 14 oz. Spray Can 7 25799 90001 9

For the most current Installation Instructions, Warranties, Technical Specifications and Approvals, visit www.mfmbp.com.

MFM Spray Adhesive cannot be shipped via Air Shipments.



Product does not contain any chemicals listed under California Proposition 65.

