

MFM Building Products Corp. manufactures a wide range of innovative waterproofing products for the building industry. Founded in 1961, MFM products are engineered for superior performance and ease of installation.

DESCRIPTION

WindowWrap® White (W3 Tape) is a self-adhering, self-sealing waterproofing tape designed for use around windows and doors, sealing building seams and general construction. It is composed of a white polymer film coated with an aggressive rubberized asphalt adhesive. A release liner protects the adhesive and is removed as the product is installed. The rubberized adhesive self-seals around punctures such as nails, screws and staples. This advanced system bonds to the substrate to prevent damage caused by water penetration.

USES

WindowWrap® White is a multi-purpose waterproofing tape suitable for sealing around windows and doors, or in any application where the membrane is protected from long-term ultraviolet exposure. It adheres aggressively to most clean, dry substrates including metal, wood, vinyl, house wrap and masonry.

FEATURES

WindowWrap® White offers the contractor and property owner these extra features:

- Uniform thickness
- Self-seals around fasteners including nails, staples and screws
- Prevents water, air, insect and noise infiltration
- Reduces potential for mold or mildew
- Eliminates leaks – multiple layers of protection seal out water
- Rubberized asphalt adhesive won't crack or dry
- Aggressively adheres to most building materials
- Comes in shrink-wrapped and labeled rolls

GENERAL INSTALLATION NOTES

This is a summary of how the product is installed. Complete Installation Instructions are available at www.mfmbp.com.

- Surface must be clean, dry and free from oil
- Apply in clear, dry weather above 35°F
- For cooler temperatures, or to improve adhesion, use MFM Low-VOC Spray Adhesive™
- Measure and cut tape to length for ease in handling, allowing 3" to 6" for overlaps
- Can be adhered directly to the sheathing or over house wrap – always apply directly to sheathing on header
- Do not seal the bottom flange to the sheathing
- Peel off release liner and stick tape to surface, applying uniform pressure with a hand roller to the entire surface
- Clean, dry wood and metal surfaces do not require priming
- It may be necessary to prime masonry and weathered surfaces with an asphalt-based primer before installation – masonry must be fully cured
- Store product in carton away from water and sunlight
- **DO NOT** expose tape to direct sunlight for more than 30 days
- **DO NOT** install over flexible vinyl gaskets
- If using caulking, use an MFM-approved caulk as listed on our Primers and Sealants Tech Bulletin posted at www.mfmbp.com
- Installer is responsible for compatibility with caulks and sealants



PRODUCT DATA

Material Color	White
Roll Sizes	4", 6" x 75'
Carton Weight	43 lbs
Rolls per Carton	9, 6
Area per Carton	225 ft ²
Cartons per Pallet	30
Minimum Installation Temperature	>35°F
Service Temperature	-20°F – 170°F

TECHNICAL SPECIFICATIONS

Property	Test Method	Result*
Material Thickness	ASTM D 3767	25 Mils Nom.
Pliability	AAMA 711	Pass
Vapor Permeance	ASTM E 96	0.008 Max
Nail Sealability	AAMA 711	Pass
Tensile MD	AAMA 711	≥143 psi
Tensile CMD	AAMA 711	≥143 psi

PRODUCT NUMBERS | UPC CODES

6" - 45W306	7 25799 10019 8
4" - 45W304	7 25799 10018 1



APPROVALS

WindowWrap® White complies with AAMA 711-07, ICC-ES AC148, Report ESR 2783, LA County (LARC/LABC) and State of California (CRC/CBC).



10-YEAR LIMITED WARRANTY

MFM Building Products Corp. (MFM) warrants materials to be free from leaks caused by defects in material or manufacturing for a period of ten (10) years from the date of purchase when applied to published directions.

For the most current Installation Instructions, Warranties, Technical Specifications and Approvals, visit www.mfmbp.com.

WindowWrap® is protected by US Patent Nos. 6,479,119 and 6,627,017. *Results listed may be the test criteria and not actual test results.