



**MFM Building Products Corp.** manufactures a wide range of innovative waterproofing products for the building industry. Founded in 1961, MFM products are engineered for superior performance and ease of installation.

## DESCRIPTION

DeckWrap PowerBond® (PB) is a self-adhering protective membrane engineered to protect decks and posts from premature rot and corrosion. DeckWrap PowerBond® features our patented PowerBond® adhesive system to adhere at temperatures as low as 25°F. In cooler temperatures, use MFM Low-VOC Spray Adhesive™ to improve adhesion. It may also be mechanically attached if desired. DeckWrap PowerBond® will self-seal around fasteners to prevent water damage. Product comes packaged in individually wrapped and labeled rolls.

## USES

DeckWrap PowerBond® should be used as a flashing over the ledger board to prevent water from entering the building. Use as a protective barrier to prevent rot, particularly between the decking and the joists.

DeckWrap PowerBond® provides a protective barrier between ACQ lumber and metal components. ACQ-treated lumber can cause untreated metal components, such as hangers and other brackets, to corrode prematurely.

Degradation of wood posts is caused by fungal growth when in contact with damp soil. Even in a concrete base, fungi can degrade posts. The product acts as a barrier between the damp soil and the post to prevent rot that typically occurs up to 6" below grade. Fungal growth requires oxygen and moisture, so below six inches, rot is negligible.

## INSTALLATION

DeckWrap PowerBond® should be installed in fair weather conditions where the ambient (surface and air) temperature is 25°F or higher. The surface must be clean, dry and smooth. Prime weathered wood surfaces with an MFM-approved primer.

Roll surface with a hand roller to ensure good adhesion. DeckWrap PowerBond® should be applied between all wood surfaces where moisture will accumulate. End laps should be a minimum of 3" between sections and rolled firmly.

Please read complete Installation Instructions at [www.mfmbp.com](http://www.mfmbp.com).

## WARNINGS

- Store in a cool dry place in original carton until ready to use
- Keep product out of direct sunlight
- Membrane should be covered within 30 days of installation
- **DO NOT** use solvent-based or silicone caulking
- **DO NOT** install over solvent-based sealants unless fully cured – active solvents may liquefy bottom adhesive surface
- Installer is responsible for compatibility with caulks and sealants

## PRODUCT DATA

Material Thickness	25 Mills
Material Color	Black
Roll Sizes	3" x 75'   6" x 75'   12" x 25'
Carton Weight – 3" and 6"	39 lbs
– 12"	15 lbs
Rolls per Carton	12, 6, 3
Cartons per Pallet	36
Self-Sealing Properties	Yes
UV Exposure	30 Days
Installation Temperature Range	>25°F
Service Temperature	-20°F – 170°F


## PRODUCT NUMBERS | PRODUCT UPC CODES

12" - 54112	7 25799 10040 2
6" - 54106	7 25799 10039 6
3" - 54103	7 25799 10038 9

## 5-YEAR LIMITED WARRANTY

MFM Building Products Corp. (MFM) warrants materials to be free from leaks caused by defects in material or manufacturing for a period of five (5) years from the date of purchase when applied according to published directions.

**For the most current Installation Instructions, Warranties, Technical Specifications and Approvals, visit [www.mfmbp.com](http://www.mfmbp.com).**



PowerBond® is protected by U.S. Patent No. 8,603,629.